



**GOLDEN
CROWN**
TYRES

TYRE CATALOGUE



- A Company Established in Year 1958
- No. 1 Tyre Manufacturer in China
- No. 9 of Top 75 Global Tyre Manufacturers in Year 2023
- Sale Revenue Reached USD4.2 Billion in Year 2022



CONTENTS





Long Haul



Long Haul



- Super value tyre for long haul application
- Stone ejector platforms prevent tread damage from stone drilling
- Four main straight grooves guarantee excellent drainage ability and even wear resulting in long tread life



AT167

- : Recommendable
- : Available



- High cost performance tyres suitable for long haul application
- Four straight ditch designs ensure drainage performance
- High saturation pattern design enhances tyre mileage



AT196

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11.00R20 | J/18 | 152/149K | 15.0 | 8.0 | 1085 | 293 | 3550 | 7825 | 930 | 135 | 3250 | 7165 | 930 | 135 |
| 265/70R19.5 | H/16 | 140/138M | 13.0 | 7.50 | 867 | 262 | 2500 | 5510 | 775 | 112 | 2360 | 5200 | 775 | 112 |
| 265/70R19.5 | J/18 | 143/141J | 13.0 | 7.50 | 867 | 262 | 2725 | 6005 | 850 | 123 | 2575 | 5675 | 850 | 123 |
| 11R22.5 | H/16 | 148/145M | 14.2 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 14.5 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 255/70R22.5 | H/16 | 140/137M | 14.0 | 7.50 | 930 | 255 | 2500 | 5510 | 830 | 120 | 2300 | 5070 | 830 | 120 |
| 275/70R22.5 | H/16 | 148/145M | 14.0 | 8.25 | 958 | 276 | 3150 | 6940 | 900 | 130 | 2900 | 6395 | 900 | 130 |
| 295/75R22.5 | G/14 | 144/141L | 14.2 | 9.00 | 1020 | 298 | 2800 | 6175 | 760 | 110 | 2575 | 5675 | 760 | 110 |
| 295/80R22.5 | J/18 | 152/149M | 14.0 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7610 | 900 | 131 |
| 315/80R22.5 | J/18 | 154/151M(156/153L) | 14.5 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 11R24.5 | H/16 | 149/146L | 14.2 | 8.25 | 1104 | 279 | 3250 | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 295/80R22.5 | J/18 | 152/149M | 13.5 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7610 | 900 | 131 |



Long Haul



Long Haul



- High cost performance tyres suitable for long haul application
- The new formula design enhances tyre mileage and reduces tyre heat generation
- Finite element simulation analysis, More uniform distribution of tyre contact pressure, improve uneven wear performance



AT186

- : Recommendable
- : Available



- Super value tyre for long haul application
- Wide base multi-rib trailer tyres with durable compound
- Improved tread design promises outstanding stability with optimized footprint and better tyre life



AT131

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | | Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|------|-------|-------|-------|---|
| | | | | | | | Single | | | | Dual | | | | | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) | |
| 315/80R22.5 | L/20 | 157/154K | 13.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 | 385/65R22.5 | L/20 | 160K(158L) | 15.5 | 11.75 | 1072 | 389 | 4500 | 9920 | 900 | 130 | - | - | - | - |



Long Haul



Long Haul



- Super value tyre suitable for steer and trailer axle
- Multi kerf provides outstanding traction on wet and snow road surface
- Four grooves with zigzag designed provide excellent groove crack prevention



AZ170

- : Recommendable
- : Available



- Super value tyre for long haul application
- Improved tread compound and tyre casing provide super balance between cost and performance



AT161

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 385/55R22.5 | L/20 | 160K(158L) | 13.0 | 12.25 | 996 | 386 | 4500 | 9920 | 900 | 130 | - | - | - | - |
| 385/65R22.5 | L/20 | 160K | 13.5 | 11.75 | 1072 | 389 | 4500 | 9920 | 900 | 130 | - | - | - | - |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145M | 15.5 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 15.5 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 295/80R22.5 | J/18 | 152/149M | 15.0 | 9.00 | 1044 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 315/80R22.5 | J/18 | 154/151M(156/153L) | 15.0 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 315/80R22.5 | L/20 | 157/154K | 15.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |



Long Haul



Long Haul



- Super value tyre for long haul application
- Straight simple rib pattern improves even wearing and efficient water evacuation for excellent wet traction and handling
- Cross rib sipes slice through water for solid control on wet roads



● : Recommendable
● : Available

AT160



- Super value tyre for long haul application
- Optimized block design prevents retaining objects for improved damage resistance
- Strong casing resists cuts and punctures for enhanced toughness and long casing life



● : Recommendable
● : Available

AD178

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|---------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145M | 14.2 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 11R24.5 | H/16 | 149/146L | 14.2 | 8.25 | 1104 | 279 | 3250 | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145L | 20.6 | 8.25 | 1065 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 295/75R22.5 | G/14 | 144/141L | 20.6 | 9.00 | 1020 | 298 | 2800 | 6175 | 760 | 110 | 2575 | 5675 | 760 | 110 |
| 11R24.5 | H/16 | 149/146L | 20.6 | 8.25 | 1116 | 279 | 3250 | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |



Long Haul



Long Haul



NEW

- High cost performance tyres suitable for long haul application
- Classic block pattern, Better driving performance and grip performance
- Wider tread to increase tyre mileage



AD122

- : Recommendable
- : Available



- Super value tyre for long haul application
- Special tread compound and tyre casing offers good tyre mileage
- Computer designed tread guarantees good traction for highway service in all season conditions



AD153

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 295/80R22.5 | J/18 | 152/149M | 18.0 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 275/80R22.5 | H/16 | 149/146L | 17.0 | 8.25 | 1012 | 276 | 3250 | 7165 | 850 | 123 | 3000 | 6610 | 850 | 123 |
| 295/80R22.5 | J/18 | 152/149L | 19.0 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |



- Super value tyre for regional application
- Wide base all routes trailer tyres with durable compound
- Good damage protection and even wear profile feature outstanding performance in all conditions



AT132

● : Recommendable
● : Available



- Super value tyre for regional application
- Five ribs ensure excellent comfort and outstanding traction on wet and dry surfaces
- Zig-zag pattern allows better tension distribution in tread grooves for even wear



AZ128

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | | Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|---------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|------|-------|-------|-------|-----|
| | | | | | | | Single | | | | Dual | | | | | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) | |
| 385/65R22.5 | L/20 | 160K(158L) | 15.5 | 11.75 | 1072 | 389 | 4500 | 9920 | 900 | 130 | - | - | - | - | 11R22.5 | H/16 | 148/145L | 15.0 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |



- Super value tyre for regional application
- Four ribs design provides excellent footprint and more contact on the road surface
- Special tyre casing and compound offer great value by longer mileage with less cost



AZ171

● : Recommendable
● : Available



- High cost performance tyres suitable for regional application
- V-shaped stepped pattern groove design, prevention of stone inclusion and stone removal, Prevent groove cracking
- Latest comprehensive road condition tyre tread formula, Balancing tear resistance and heat generation, Better mileage for comprehensive road conditions



AZ189

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145L | 15.5 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 16.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 295/80R22.5 | J/18 | 152/149M | 16.0 | 9.00 | 1044 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 315/80R22.5 | J/18 | 154/151M(156/153L) | 16.0 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 315/80R22.5 | L/20 | 157/154K | 16.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 315/80R22.5 | L/20 | 157/154K | 13.5 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |
| 12R22.5 | J/18 | 152/149L | 13.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 11R22.5 | H/16 | 146/143M | 12.5 | 8.25 | 1054 | 279 | 3000 | 6610 | 830 | 120 | 2725 | 6005 | 830 | 120 |



- Super value tyre for regional application
- Non-directional tread design for easy operating
- Open lug design helps provide traction in wet or snowy conditions



CM187

● : Recommendable
● : Available



- Super value tyre for regional application
- Aggressive tread blocks with special tread compound provide good traction on paved roads for price-oriented customers
- Special tread design promises remarkable footprint and even wear to extend tread life



AD156

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|----------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 9.00R20 | H/16 | 144/142K | 14.5 | 7.0 | 1019 | 259 | 2800 | 6175 | 900 | 130 | 2650 | 5840 | 900 | 130 |
| 11.00R20 | J/18 | 152/149K | 16.0 | 8.0 | 1085 | 293 | 3550 | 7825 | 930 | 135 | 3250 | 7165 | 930 | 135 |
| 12R22.5 | J/18 | 152/149L | 18.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145L | 20.6 | 8.25 | 1065 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 19.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 295/80R22.5 | J/18 | 152/149M | 19.0 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 11R24.5 | H/16 | 149/146L | 20.6 | 8.25 | 1116 | 279 | 3250 | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |



Regional



Regional



- Super value tyre for regional application
- Special tread compounding ensuring longer wear life and service life
- Wide shoulder design helps even wear and longer mileage



AZ102

- : Recommendable
- : Available



- Super value tyre for regional application
- Four ribs ensure even wear and comfortable riding
- Siped zig-zag rib helps improve traction on wet and muddy surface



AZ166

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|----------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 12.00R24 | L/20 | 160/157K | 14.0 | 8.5 | 1226 | 315 | 4500 | 9920 | 900 | 131 | 4125 | 9090 | 900 | 131 |
| 12.00R24 | L/20 | 160/157K | 15.0 | 8.5 | 1226 | 315 | 4500 | 9920 | 900 | 131 | 4125 | 9090 | 900 | 131 |



Mixed Service



- Super value tyre for regional&mixed service application
- Variable groove angle for long mileage
- Stone ejector in the groove protect belt from stone drilling
- Zig-zag groove help improve traction on wet and muddy surface



AZ183

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 10.00R20 | J/18 | 149/146J | 15.5 | 7.5 | 1054 | 278 | 3250 | 7160 | 930 | 135 | 3000 | 6610 | 930 | 135 |
| 11.00R20 | J/18 | 152/149K | 16.0 | 8.0 | 1085 | 293 | 3550 | 7825 | 930 | 135 | 3250 | 7165 | 930 | 135 |
| 12.00R20 | J/18 | 154/151K | 16.5 | 8.5 | 1125 | 315 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 11R22.5 | H/16 | 148/145L | 15.0 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 15.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 13R22.5 | J/18 | 156/151K | 15.0 | 9.75 | 1124 | 320 | 4000 | 8820 | 875 | 128 | 3450 | 7610 | 875 | 128 |
| 295/80R22.5 | J/18 | 152/149L | 15.0 | 9.00 | 1044 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 315/80R22.5 | J/18 | 154/151M(156/153L) | 15.0 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 11R24.5 | H/16 | 149/146L | 15.0 | 8.25 | 1104 | 279 | 3250 | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |



Mixed Service



- High cost performance tyres suitable for regional application
- Wider and deeper tread to increase tyre mileage
- Crisscrossing patterned steel sheets, Excellent grip and slippery performance



AZ137

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 315/80R22.5 | J/18 | 154/151M(156/153L) | 16.5 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |



Mixed Service



- Super value tyre for regional&mixed service application
- Wide, deep tread helps provide long tread life in regional conditions
- Zig-zag ribs ensure even wear and grip on wet, dry and snowy roads



AZ188

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145M | 15.5 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 16.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 315/80R22.5 | J/18 | 154/151M(156/153L) | 15.5 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 315/80R22.5 | L/20 | 157/154K | 15.5 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |



Mixed Service



- High cost performance tyres suitable for regional&mixed service application
- V-shaped stepped pattern groove design, prevention of stone inclusion and stone removal, Prevent groove cracking
- tyre shoulder horizontal pattern design, Improve heat dissipation performance, better grip and handling performance



AZ118

- : Recommendable
- : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 315/80R22.5 | L/20 | 157/154K | 14.5 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |
| 12R22.5 | J/18 | 152/149L | 14.5 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 11R22.5 | H/16 | 148/145L | 13.0 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



AZ026

● : Recommendable
● : Available



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



AZ126

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|----------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 10.00R20 | J/18 | 149/146J | 16.0 | 7.5 | 1054 | 278 | 3250 | 7160 | 930 | 135 | 3000 | 6610 | 930 | 135 |
| 11.00R20 | J/18 | 152/149K | 16.0 | 8.0 | 1085 | 293 | 3550 | 7825 | 930 | 135 | 3250 | 7165 | 930 | 135 |
| 12.00R20 | J/18 | 154/151K | 17.5 | 8.5 | 1125 | 315 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 315/80R22.5 | J/18 | 154/151M(156/150L) | 15.5 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 315/80R22.5 | L/20 | 157/154K | 15.5 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



AZ126T

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|--------------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 11R22.5 | H/16 | 148/145M | 16.8 | 8.25 | 1054 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149L | 16.0 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 295/80R22.5 | J/18 | 152/149L | 16.0 | 9.00 | 1044 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 315/80R22.5 | J/18 | 154/151M(156/150L) | 16.0 | 9.00 | 1076 | 312 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 315/80R22.5 | L/20 | 157/154K | 16.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |
| 11R24.5 | H/16 | 149/146L | 16.8 | 8.25 | 1104 | 279 | 3250 | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



CR926T

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|----------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 12.00R24 | L/20 | 160/157K | 16.0 | 8.5 | 1226 | 315 | 4500 | 9920 | 900 | 131 | 4125 | 9090 | 900 | 131 |



Mixed Service



- Super value tyre for mixed service application
- Drive axle tyre applicable for mud and sand terrain with short on high-way use
- Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel
- Special tread compounds resist chipping, chunking and tearing



EZ033

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 9.00R20 | H/16 | 144/142K | 17.0 | 7.0 | 1019 | 259 | 2800 | 6175 | 900 | 130 | 2650 | 5840 | 900 | 130 |
| 12.00R24 | L/20 | 160/157K | 16.0 | 8.5 | 1226 | 315 | 4500 | 9920 | 900 | 131 | 4125 | 9090 | 900 | 131 |
| 315/80R22.5 | L/20 | 157/154K | 16.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |



Mixed Service



- Super value tyre for mixed service application
- Aggressive blocks provides outstanding traction on rough roads
- Open shoulder tread design help promote self-cleaning ability



MD101

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 13R22.5 | J/18 | 156/151K | 19.0 | 9.75 | 1136 | 320 | 4000 | 8820 | 875 | 128 | 3450 | 7610 | 875 | 128 |
| 315/80R22.5 | L/20 | 157/154K | 19.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |



Mixed Service



- Super value tyre for mixed service application
- Aggressive lug design with larger blocks at tread center provides excellent traction
- Open shoulder tread design improves self-cleaning capacity for ease of maintenance



EZ175/EZ175A

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|---------------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 10.00R20 | J/18 | 149/146D | 20.0 | 7.5 | 1065 | 278 | 3250 | 7160 | 930 | 135 | 3000 | 6610 | 930 | 135 |
| 11.00R20 | J/18 | 152/149D | 20.0 | 8.0 | 1096 | 293 | 3550 | 7825 | 930 | 135 | 3250 | 7165 | 930 | 135 |
| 12.00R20 | J/18 | 154/151F | 21.0 | 8.5 | 1125 | 315 | 3750 | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 11R22.5 | H/16 | 148/145J | 19.5 | 8.25 | 1065 | 279 | 3150 | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 12R22.5 | J/18 | 152/149F | 19.5 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 295/80R22.5 | J/18 | 152/149J | 20.0 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 315/80R22.5(EZ175A) | L/20 | 157/154K | 16.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |



Mixed Service



- High cost performance tyres suitable for mixed service application
- The consistent and sturdy pattern design at the center of the tread, Reduce tyre tread damage and improve tyre life
- The tread adopts a wear-resistant and cutting resistant formula, Improve the comprehensive performance of tyres



EZ177

● : Recommendable
● : Available

| Size | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure | | | | | | | |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|---|-------|-------|-------|------|-------|-------|-------|
| | | | | | | | Single | | | | Dual | | | |
| | | | | | | | (kg) | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 12R22.5 | J/18 | 152/149K | 19.5 | 9.00 | 1085 | 300 | 3550 | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 315/80R22.5 | L/20 | 157/154K | 20.0 | 9.00 | 1076 | 312 | 4125 | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |
| 295/80R22.5 | J/18 | 152/149J | 19.5 | 9.00 | 1050 | 298 | 3550 | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |




ZC-Rubber America Inc.

ZC-Rubber Mexican
(under construction)


ZC-Rubber Brasil Co. Ltd.


ZC-Rubber Europe Technical Center
ZC-Rubber Europe GmbH


ZC-Rubber Thailand Co. Ltd.

ZC-Rubber Indonesia
(under construction)


ZC-Rubber HQ
ZC-Rubber Tianjin
ZC-Rubber Chaoyang
ZC-Rubber Jiande
ZC-Rubber Qingquan
ZC-Rubber Yonggu
ZC-Rubber Anji
ZC-Rubber Jintan
ZC-Rubber Recycling
Tech. Co. Ltd.
Hangzhou ZC-Rubber
Auto Space Co. Ltd.



ZHONGCE RUBBER GROUP CO., LTD.